


AK-C7412

Wireless disinfectable Medical Keyboard with numpad and touchpad



Models may vary from the image shown

The AK-C7412 keyboard series is particularly suitable for use in hospitals, doctors' offices and microbiology laboratories, as well as in industrial and administrative applications, thanks to its cleaning and disinfection capability.

The silicone membrane with the ultra-flat key profile reliably protects the keyboard against the ingress of dirt and liquids and enables thorough wipe disinfection. In addition, the closed, gap-free surface provides effective protection against cross-contamination, the spread of germs and the formation of biofilms.

Thanks to the fully sealed membrane, the AK-C7412 meets the requirements for protection class IP65. The hygiene & medical keyboard is approved for clinical wipe disinfection with all common cleaning/disinfection agents in accordance with the VAH and DGHM guidelines.

Another advantage is the "CleanFunction", which allows the keypad to be locked during cleaning ("FN" + "Clean on/off").

FUNCTION AND PERFORMANCE

- Hygiene Keyboard for Clinical Wipe Disinfection
- Available as a wired variant and a rechargeable wireless variant

- Clinical Wipe Disinfection with all common Disinfectants according to German Guidelines VAH/DGHM
- Utmost Writing Comfort by Scissors Balancing Technology
- Perfect writing in Hygiene Critical Applications
- Exchangeable membrane for automated disinfection at 93°C and 134°C (in addition to wipe disinfection)
- CleanFunction allows to switch off Keys during Cleaning Process
- 4 Threaded Holes for VESA Mounting
- German Brand Product

TECHNICAL DATA

Colour:	white
Weight main product:	580 g
Weight of product without packaging:	590 g
Weight of product incl. packaging:	760 g
Weight of master carton incl. content:	13,300 g
Content of master carton (pieces):	20
Dimensions product without packaging:	365 mm x 139 mm x 19 mm
Dimensions product incl. packaging:	380 mm x 205 mm x 25 mm
Dimensions master carton:	400 mm x 273 mm x 447 mm
Storage temperature:	-20 °C - 60 °C
Working temperature:	0 °C - 50 °C
Product approvals:	<ul style="list-style-type: none">• CE• EU RoHS• FCC• EN60601-1-2-2015 (IEC 4th edition)
System Requirements-Hardware:	USB-A

Operating system: All operating systems that support USB keyboard interface

Scope of delivery:

- Keyboard
- Manual
- Dongle
- USB-A to USB-C Cable

Reliability: MTBF 90: > 10 Mio.

USB dongle: yes

Wireless range: 10 m

Number of batteries: 1

Battery type: Li-Ion

Switching characteristics: tactile

Max. current consumption (mA) of keyboard:

11 mA

Actuating force (cN): 60 cN

Total Key Travel: 2,5 mm

Key labeling: Silk screen printing on silicon membrane

Number of keys: 105

Special key functions:

- FN Key
- CleanFunction

Status LEDs: in housing

Key technology: Scissor

Keycap material: ABS

Reprocessing:

- Recommended for Wipe Disinfection
- Approved for wipe disinfection according to CDC Guideline for Disinfection and Sterilization in Healthcare Facilities with EPA-registered disinfecting products
- Removable Membrane suitable for Machine Disinfection
- Water Proof (IP65) with Detachable Cable

EAN: 7061115434657

Protection class: Standard

Warranty: 2 years warranty

Layout: PN (PanNordic)

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.